



Article Number: 151-01450

Ratchet P-Clamp, .52"-.77" Bundle Dia, 15° Short, .51" Hole Dia, PA66HIRHSUV/ST/ZN, Black, 280/ctn Description:

Base Data		
	Lacel Order Niverke	454.04450
	Local Order Number	151-01450
	Туре	RCB15SM12
	Color	Black (BK)
	Features and Benefits	<ul> <li>One-piece ratchet closure design allows for easy installation during pre- or final assembly.</li> <li>Four sizes and multiple configurations handle a wide range of diameters and applications, reducing part inventory.</li> <li>Clamp interior is designed to guide and center bundle to reduce pinching.</li> <li>Easy release feature allows for quick adjustments and maintenance.</li> <li>Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.</li> <li>Steel mounting plate tolerates high torque mounting and is treated to resist chemicals and salt spray.</li> </ul>
	Quantity Per	carton
	Product Description	The Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The one-piece adjustable clamp can be closed by hand to the desired diameter. The release feature provides easy and nondestructive removal of cables simply by using a flat-head screwdriver. This nondestructive release allows the clamp to be reused without removing or replacing any bolts or screws. The Ratchet P-Clamp is offered in four sizes and multiple mounting configurations.
	Short Description	Ratchet P-Clamp, .52"77" Bundle Dia, 15° Short, .51" Hole Dia, PA66HIRHSUV/ST/ZN, Black, 280/ctn
Product Dimensions		
	Minimum Tensile Strength (Imperial)	100.0lbs
	Minimum Tensile Strength (Metric)	445.0N
	Length L (Imperial)	4.55"
	Length L (Metric)	115.6mm
	Length L2 (Imperial)	3.42"
	Fixation Method	Screw Mounting
	Length L2 (Metric)	86.9mm
	Variant	15° Short
	Width W (Imperial)	1.37"

generated on:

4/28/2017

## 151-01450



Product Dimensions         Width W (Metric)         34.9mm           Cable Tie Width Max. (Imperial)         0.52"           Cable Tie Width Max. (Metric)         13.2mm           Width W2 (Imperial)         1.181"           Width W2 (Metric)         30.0mm           Bundle Diameter Min. (Imperial)         0.5"           Bundle Diameter Min. (Metric)         12.7mm           Bundle Diameter Max. (Imperial)         0.77"           Bundle Diameter Max. (Metric)         19.5mm           Mounting Hole Diameter D (Imperial)         0.510"           Mounting Hole Diameter D (Metric)         M12           Mounting Hole Centers (Imperial)         2.22"           Stud Size (Metric)         M12           Material and Specifications         Material           Material         Steel (ST)	Product		
Cable Tie Width Max. (Imperial)  Cable Tie Width Max. (Metric)  Width W2 (Imperial)  Width W2 (Metric)  Bundle Diameter Min. (Imperial)  Bundle Diameter Min. (Imperial)  Bundle Diameter Max. (Imperial)  Bundle Diameter Max. (Imperial)  Bundle Diameter Max. (Imperial)  O.77"  Bundle Diameter Max. (Metric)  Mounting Hole Diameter D (Imperial)  Mounting Hole Diameter D (Metric)  Mounting Hole Centers (Imperial)  Stud Size (Metric)  M12  Material and Specifications		Width W (Metric)	34.9mm
Width W2 (Imperial)  Width W2 (Metric)  Bundle Diameter Min. (Imperial)  Bundle Diameter Min. (Metric)  Bundle Diameter Max. (Imperial)  Bundle Diameter Max. (Imperial)  Bundle Diameter Max. (Metric)  Bundle Diameter Max. (Metric)  Bundle Diameter D (Imperial)  Mounting Hole Diameter D (Imperial)  Mounting Hole Diameter D (Metric)  M12  Mounting Hole Centers (Imperial)  Stud Size (Metric)  M12  Material and Specifications		Cable Tie Width Max. (Imperial)	0.52"
Width W2 (Metric) 30.0mm  Bundle Diameter Min. (Imperial) 0.5"  Bundle Diameter Min. (Metric) 12.7mm  Bundle Diameter Max. (Imperial) 0.77"  Bundle Diameter Max. (Metric) 19.5mm  Mounting Hole Diameter D (Imperial) 0.510"  Mounting Hole Diameter D (Metric) M12  Mounting Hole Centers (Imperial) 2.22"  Stud Size (Metric) M12  Material and Specifications		Cable Tie Width Max. (Metric)	13.2mm
Bundle Diameter Min. (Imperial)  Bundle Diameter Min. (Metric)  Bundle Diameter Max. (Imperial)  Bundle Diameter Max. (Imperial)  Bundle Diameter Max. (Metric)  Bundle Diameter Max. (Metric)  19.5mm  Mounting Hole Diameter D (Imperial)  Mounting Hole Diameter D (Metric)  Mounting Hole Centers (Imperial)  2.22"  Stud Size (Metric)  M12  Material and Specifications		Width W2 (Imperial)	1.181"
Bundle Diameter Min. (Metric)  Bundle Diameter Max. (Imperial)  Bundle Diameter Max. (Metric)  Bundle Diameter Max. (Metric)  Mounting Hole Diameter D (Imperial)  Mounting Hole Diameter D (Metric)  Mounting Hole Centers (Imperial)  2.22"  Stud Size (Metric)  M12  Material and Specifications		Width W2 (Metric)	30.0mm
Bundle Diameter Max. (Imperial) 0.77"  Bundle Diameter Max. (Metric) 19.5mm  Mounting Hole Diameter D (Imperial) 0.510"  Mounting Hole Diameter D (Metric) M12  Mounting Hole Centers (Imperial) 2.22"  Stud Size (Metric) M12  Material and Specifications		Bundle Diameter Min. (Imperial)	0.5"
Bundle Diameter Max. (Metric)  Mounting Hole Diameter D (Imperial)  Mounting Hole Diameter D (Metric)  Mounting Hole Centers (Imperial)  Stud Size (Metric)  Material and Specifications		Bundle Diameter Min. (Metric)	12.7mm
Mounting Hole Diameter D (Imperial)  Mounting Hole Diameter D (Metric)  Mounting Hole Centers (Imperial)  Stud Size (Metric)  Material and Specifications  Mounting Hole Diameter D (Metric)  M12  M12		Bundle Diameter Max. (Imperial)	0.77"
Mounting Hole Diameter D (Metric)  Mounting Hole Centers (Imperial)  Stud Size (Metric)  M12  Material and Specifications		Bundle Diameter Max. (Metric)	19.5mm
Mounting Hole Centers (Imperial) 2.22"  Stud Size (Metric) M12  Material and Specifications		Mounting Hole Diameter D (Imperial)	0.510"
Stud Size (Metric) M12  Material and Specifications		Mounting Hole Diameter D (Metric)	M12
Material and Specifications		Mounting Hole Centers (Imperial)	2.22"
Specifications		Stud Size (Metric)	M12
Material Steel (ST)			
		Material	Steel (ST)
Material Shortcut ST		Material Shortcut	ST
Flammability UL 94 HB		Flammability	UL 94 HB
Operating Temperature -40°F to +257°F (-40°C to +125°C)		Operating Temperature	-40°F to +257°F (-40°C to +125°C)
ROHS Compliant Yes		ROHS Compliant	Yes
Stamping Material Steel (ST)		Stamping Material	Steel (ST)
Logistic and Packaging			
Package Quantity (Imperial) 280		Package Quantity (Imperial)	280
Package Quantity (Metric) 280		Package Quantity (Metric)	280
Customs Number(Schedule B) 3926909987		Customs Number(Schedule B)	3926909987

generated on: 4/28/2017